

ТЕМПОМАТИС 4 urinal valve

Арт. 430PBOX-430006

Electronic with integrated battery







ОПИСАНИЕ

ТЕМПОМАТИС 4 urinal valve - Арт. 430PBOX-430006


Electronic valve for waterproof, recessed individual urinals:
 123 6V Lithium battery-operated.
 Satin finish stainless steel wall plate 145 x 145mm with integrated electronics.
 Waterproof recessing housing:
 - Collar with waterproof seal.
 - Hydraulic connection to the outside and maintenance from the front.
 - Adjusts to all types of installation (rails, solid walls, panels).
 - Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 83mm).
 - Suitable for standard or "pipe-in-pipe" supply.
 - Stopcock and flow rate adjustment, filter and solenoid valve are all integrated and accessible from the front.
 - ТЕМПОМАТИС 4 urinal valve F1/2" is compatible with sea water and grey water.
 - Supplied in 2 kits: secure system flush without sensitive elements.
 - Shock-resistant infrared presence detection sensor.
 Detection delay is 10 seconds.
 3 programmes (rinsing volume can be set according to urinal type).
 High-frequency mode (exclusive to DELABIE):
 - Short rinse after each user.
 - Additional rinse at the end of the busy period.
 Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use: prevents vacuums.
 Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted.
 Connection with Ø 35mm connection washer (for standard urinals) or 1/2" brass connection (for urinals supplied by flexible).
 For use with neck tube 752430 or 757430.
 10-year warranty.

ПРЕИМУЩЕСТВА

-  3 rinsing programmes and high-frequency mode
-  Total hygiene: no manual contact
-  Duty flush prevents proliferation of bacteria
-  Waterproof recessing housing adjusts to any installation

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

ТЕМПОМАТИС 4 urinal valve - Арт. 430PBOX-430006

Соединение	F1/2"
Технология	Electronic
Глубина	83 - 190 mm
Ширина	145mm
Расход	0.15 L/sec
НОРМЫ И СЕРТИФИКАЦИЯ	 
ГАРАНТИИ	

