

TEMPOMATIC direct flush valve

Арт. 463030

For TEMPOMATIC multifunction unit







ОПИСАНИЕ

TEMPOMATIC direct flush valve - Арт. 463030

Cross wall electronic direct flush valve:
 Mains supply with 1" solenoid valve.
 230/12V transformer.
 IP65 independent electronic unit.
 For cross wall installation on walls ≤ 30 mm.
 Shock-resistant infrared presence detection sensor.
 Voluntary activation (when hand is detected ~ 10 cm in front of the sensor) or automatic flush when the user leaves.
 Time flow ~ 7 seconds, can be adjusted from 3 - 12 seconds.
 Detection distance, flow rate and flush volume can be adjusted.
 Stopcock FF1".
 Vacuum breaker $\varnothing 32$ mm
 Connection washer $\varnothing 32/55$ mm.
 Wall plate flush to the wall.
 Threaded rod can be cut to size.
 Base flow rate: 1 L/sec.
 Suitable for Rimless WC pans.
 10-year warranty.

ПРЕИМУЩЕСТВА

-  Total hygiene: operate without manual contact
-  Direct flush: no stagnant water
-  Voluntary or automatic flush
-  Cross wall installation

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

TEMPOMATIC direct flush valve - Арт. 463030

Подключение	230/12V mains supply
Соединение	1"
Технология	Electronic
Длина	30mm
НОРМЫ И СЕРТИФИКАЦИЯ	 
ГАРАНТИИ	

