

TEMPOFLUX 2 direct flush valve

Арт. 762901

Time flow valve for direct flush 6L single flush



ОПИСАНИЕ




TEMPOFLUX 2 direct flush valve - Арт. 762901

Recessed time flow valve for direct flush:
 Multipurpose recessing housing.
 Chrome-plated metal wall plate Ø 195mm.
 Recessing depth can be adjusted from 0 - 20mm.
 6L single flush.
 Soft-touch operation.
 Vacuum breaker.
 Integrated stopcock and flow rate / flush volume adjuster.
 Solid brass body.
 Chrome-plated metal push-button.
 In-line inlet M3/4".
 Outlet connection for PVC tube Ø 26/32mm.
 Acoustic level complies with European standard EN 12541 class II.




This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).
 10-year warranty.

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

TEMPOFLUX 2 direct flush valve - Арт. 762901

Соединение	3/4"
Технология	Time flow
Расход	6l
НОРМЫ И СЕРТИФИКАЦИЯ	 
ГАРАНТИИ	

ПРЕИМУЩЕСТВА

-  Soft-touch operation
-  Direct flush: no stagnant water
-  Wall recessed installation
-  Powerful flush and available immediately

