

SECURITHERM shower panel

Арт. 792310

Thermostatic time flow


ОПИСАНИЕ

SECURITHERM shower panel - Арт. 792310

Thermostatic time flow shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
Concealed inlet via flexibles M1/2".
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
Thermal shocks are possible.
Soft-touch operation.
Time flow ~30 seconds.
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
Concealed fixings.
Filters and non-return valves.
10-year warranty.





ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

SECURITHERM shower panel - Арт. 792310

Соединение	M1/2"
Технология	Time flow
Высота	1050mm
Глубина	65mm
Ширина	210mm
Расход	6 lpm
Ограничение температуры	Thermostatic
Покрытие	Aluminium
НОРМЫ И СЕРТИФИКАЦИЯ	   
ГАРАНТИИ	



ПРЕИМУЩЕСТВА

-  Thermostatic control
-  Instant shut-off if cold water fails
-  Water savings up to 80%
-  Aluminium panel, brass controls

