

SECURITHERM shower panel

Арт. 792400

Electronic battery-operated thermostatic

ОПИСАНИЕ

SECURITHERM shower panel - Арт. 792400

Thermostatic electronic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
With top inlet, via in-line stopcocks M1/2".
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
Thermal shocks are possible.
Battery-operated with 223 6V Lithium battery.
Infrared presence detection. Shower starts when hand is 4cm from the sensor.
Shuts off on demand or automatically after ~60 seconds.
Duty flush (~60sec. every 24hr after the last use).
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
Concealed fixings.
Filters and non-return valves.
10-year warranty.





ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

SECURITHERM shower panel - Арт. 792400

Подключение	6V battery
Соединение	M1/2"
Технология	Electronic
Высота	1050mm
Глубина	65mm
Ширина	210mm
Расход	6 lpm
Ограничение температуры	Thermostatic
Покрытие	Aluminium
НОРМЫ И СЕРТИФИКАЦИЯ	   
ГАРАНТИИ	



ПРЕИМУЩЕСТВА

-  Total hygiene: operate without manual contact
-  Automatic anti-bacterial duty flush
-  Thermostatic control
-  Instant shut-off if cold water fails

