

## SECURITHERM Securitouch thermostatic shower mixer

Арт. H9769

SECURITHERM Securitouch thermostatic shower mixer



### ОПИСАНИЕ

**SECURITHERM Securitouch thermostatic shower mixer - Арт. H9769**





SECURITHERM dual control thermostatic shower mixer with:

- No non-return valves on the inlets (reduced bacterial proliferation). No risk of cross flow between hot and cold water.
- Anti-scalding failsafe: shuts off immediately if cold water supply fails (and vice versa).
- Securitouch thermal insulation prevents burns.
- Scale-resistant thermostatic cartridge for temperature adjustment.
- ¼-turn ceramic head for flow rate adjustment.
- Temperature control up to 41 °C.
- Double temperature limiter: 1st limiter set at 39 °C, 2nd limiter set at 41 °C.
- Thermal shocks are possible without removing the control knob or shutting off the cold water supply.
- Flow rate limited to 9 lpm at 3 bar.
- Ergonomic controls.
- M½" shower outlet.
- M¾" inlets with integrated filters.

Mixer supplied with STOP/CHECK wall connectors M½" M¾", ideal for hospitals.

10-year warranty.

### ПРЕИМУЩЕСТВА

-  SECURITHERM: Anti-scalding safety
-  No non-return valves on inlets
-  Securitouch thermal insulation prevents burns
-  Thermostatic: total temperature stability

### ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

**SECURITHERM Securitouch thermostatic shower mixer - Арт. H9769**

Соединение	M1/2"
Технология	SECURITHERM dual control thermostatic mixer, Securitouch, no-non-return valves
Глубина	95 mm
Длина	260mm
Расход	8 lpm
Ограничение температуры	41 °C
Покрытие	Chrome-plated brass
НОРМЫ И СЕРТИФИКАЦИЯ	  
ГАРАНТИИ	

